



# REPORT

Technical Report: (5106)010-0101 REVISION

Page 1 of 1  
May 4, 2006



| Index    |         |
|----------|---------|
| Cover    | 1 Page  |
| Report   | 4 Pages |
| Protocol | 9 Pages |
| Exhibits | 1 Page  |
| Other    | N/A     |

Bureau Veritas

Consumer Products Services, Inc.

100 Northpointe Parkway Buffalo, NY 14228-1884 USA

Tel 716 505 3300 Fax 716 505 3301 [www.cps.bureauveritas.com](http://www.cps.bureauveritas.com)

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.cps.bureauveritas.com> is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from the date of issuance of this report to notify us of any material error or omission caused by our negligence; provided, however, that such notice shall be in writing and specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the results of the tests.



**Technical Report: (5106)010-0101 Revision**  
Date Received: January 10, 2006

May 4, 2006  
Page 1 of 4

DIRECTORATE FOR ENGINEERING SCIENCES  
US CONSUMER PRODUCTS SAFETY COMMISSION  
4330 EAST WEST HIGHWAY  
ROOM 611  
BETHESDA, MD 20814  
UNITED STATES

|                             |  |                    |             |
|-----------------------------|--|--------------------|-------------|
| Sample Description:         | CIGARETTE LIGHTERS - R                 | Sample Size:       | 30          |
| Vendor:                     | US CONSUMER PRODUCTS SAFETY COMMISSION |                    |             |
| Manufacturer:               | FLAMEGAS LUCKY SALES INC               | Style No(s):       | 05-810-2266 |
| Buyer:                      | N/A                                    | SKN/SKU No.:       | N/A         |
| Labeled Age Grade:          | N/A                                    | PO No.:            | N/A         |
| Appropriate Age Grade:      | N/A                                    | Ref #:             | N/A         |
| Client Specified Age Grade: | N/A                                    | Country of Origin: | CHINA       |
| Grade:                      |  |                    |             |
| Tested Age Grade:           | N/A                                    | Assortment No.:    | N/A         |
| UPC Code:                   | N/A                                    |                    |             |

#### **EXECUTIVE SUMMARY:**

At the request of the client, the submitted sample was evaluated per the applicable sections of Bureau Veritas Consumer Products Services test protocol MC-4085-US, Lighters (ASTM F400).

#### **Results:**

Volumetric Displacement: ASTM F-400, Section 4.6 – The liquid portion of the fuel in the submitted sample shall not exceed 85% of the volumetric capacity of the fuel chamber. Submitted sample #11 exhibited a 88.9% liquid portion of fuel in the fuel chamber.

Cycling Burn: ASTM F400-04, Section 5.6 – The submitted sample shall be capable of withstanding a burning time of 20 seconds, repeated 10 times. After 10 cycles of 20 seconds, the submitted sample #30 experienced self-maintained ignition. (See exhibit 1)

#### **NOTE:**

- At the request of the client the labeling and refilling sections of the protocol were evaluated for reference only



US CONSUMER PRODUCTS SAFETY COMMISSION

Technical Report: **(5106)010-0101R**

May 4, 2006

Page 2 of 4

- The submitted samples did not include refilling instructions. Refilling was performed as follows:
  - Refill valve was placed face up
  - National brand butane fuel nozzle placed into filling valve and depressed two or three times with firm, even pressure, being sure not to overfill.
  - Wait at least 2 minutes before igniting lighter.
  
- At the request of the client the Lead in Surface Coatings was not tested.

**NOTE:** Revision for correction to protocol.

Bureau Veritas  
Consumer Products Services, Inc.

Mark Gerwitz, CQE, CRE  
Product Test Supervisor,  
Hardlines Department

Bureau Veritas  
Consumer Products Services, Inc.

Paul Ehrmann  
Product Test Engineer,  
Hardlines Department

/kv

cc: SHIVANI MEHTA, US CONSUMER PRODUCTS SAFETY COMMISSION



US CONSUMER PRODUCTS SAFETY COMMISSION  
 Technical Report: **(5106)010-0101R**

May 4, 2006  
 Page 3 of 4

|                              |                  |
|------------------------------|------------------|
| # of Lighters                | 30               |
| Company                      | 05-810-2266      |
| Date                         | January 23, 2006 |
| Adjustable or Non-Adjustable | A                |

|                       |    |
|-----------------------|----|
| Labeling              |    |
| Safety and Warnings   | 30 |
| Product Markings      | 30 |
| Retail Shel Packaging | 30 |

|                          |   |           |
|--------------------------|---|-----------|
| Analytical               |   | Lighter # |
| Lead in Surface Coatings | 1 | NT        |

|                          |   |           |
|--------------------------|---|-----------|
| Physical Characteristics |   | Lighter # |
| Dimensions               | 1 | 11        |
| Weight                   | 1 | 11        |

|                               |   |           |
|-------------------------------|---|-----------|
| Compatibility 28 days @ 104 F | 1 | Lighter # |
|                               |   | 9         |

|                 |    |
|-----------------|----|
| Workmanship     |    |
| External Finish | 30 |

|                             |    |   |
|-----------------------------|----|---|
| Performance                 |    | Lighter #'s   |
| Flame Generation            | 28 | 1,2,3,4,5,6,7,8,,10,12,13,14,15,16,18,19,20,21,22,23,24,25,26,27,28,29,30 |
| Flame Control               | 28 | 1,2,3,4,5,6,7,8,,10,12,13,14,15,16,18,19,20,21,22,23,24,25,26,27,28,29,30 |
| Flame Height Adjustment     | 28 | 1,2,3,4,5,6,7,8,,10,12,13,14,15,16,18,19,20,21,22,23,24,25,26,27,28,29,30 |
| Spitting Sputtering Flaring | 28 | 1,2,3,4,5,6,7,8,,10,12,13,14,15,16,18,19,20,21,22,23,24,25,26,27,28,29,30 |
| Flame Extinction            | 13 | 1,2,3,5,15,19,20,21,22,24,25,26,29  |



|                       |   |                         |    |                                     |
|-----------------------|---|-------------------------|----|-------------------------------------|
| Volumetric            | 1 | Lighter #               |    |                                     |
|                       |   | 11                      |    |                                     |
| Drop Test             |   | Lighter #               |    |                                     |
|                       |   | 24 hrs @ 14 C 3 Drops   | 2  | 1,21                                |
|                       |   | 10 Hours @ 23 C 3 Drops | 2  | 2,5                                 |
|                       |   | Section 4               | 4  | 1,2,5,21                            |
| Temperature Test      |   | Lighter #               |    |                                     |
|                       |   | 4 hours @ 65 C          | 3  | 3,20,26                             |
|                       |   | Section 4               | 3  | 3,20,26                             |
| Burning Test          |   | Lighter #               |    |                                     |
|                       |   | 10 sec @ 45 deg         | 13 | 1,2,3,5,15,19,20,21,22,24,25,26,29  |
| Continuous Burn       |   | Lighter #,s             |    |                                     |
|                       |   | 2 minute Burn           | 13 | 4,6,7,8,10,12,13,14,17,18,23,27,28  |
| Cycling Burn          |   | Lighter #,s             |    |                                     |
|                       |   | 10 cycles for 20 sec    | 13 | 1,3,5,15,16,19,20,21,22,24,26,29,30 |
|                       |   | Section 4               | 13 | 1,3,5,15,16,19,20,21,22,24,26,29,30 |
| Pressure Test         | 3 | Lighter #               |    |                                     |
|                       |   | 15,19,29                |    |                                     |
| Refilling of Lighters | 1 | Lighter #               |    |                                     |
|                       |   |                         |    |                                     |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF  
 Test Date: January 27, 2006  
 Reviewed By/Date: PE March 28, 2006

**BUREAU VERITAS TEST PROTOCOL FOR**  
**MC-4085-US**  
**Lighters (ASTM F400)**

| Evaluation                | Citation/Method             | No. Samples | Criteria   | Results   | Rating |
|---------------------------|-----------------------------|-------------|--|-----------|--------|
| <b>LABELING</b>           |                             |             |  |           |        |
| Instructions and Warnings | ASTM F400-04, Section 7.1   | All         | All lighters shall be accompanied by the appropriate instructions or warnings, or both, communicating proper method of use.  | Present   | -      |
|                           | ASTM F400-04, Section 7.2   | All         | This safety information shall be conspicuously placed on the product or on a separate brochure or pamphlet packaged with the lighters or on a product packaging at the point of sale with contrasting background color, type size, or style that makes it distinct from other information. | Present   | -      |
|                           | ASTM F400-04, Section 7.3   | All         | For all lighters, the safety information shall be accompanied in close proximity by the specific signal word "WARNING."  | Present   | -      |
|                           | ASTM F400-04, Section 7.4   | All         | For all lighters, the safety information shall contain the following statements:   | See Below | -      |
|                           | ASTM F400-04, Section 7.4.1 | All         | "Keep away from children" or "keep out of reach of children"   | Present   | -      |
|                           | ASTM F400-04, Section 7.4.2 | All         | Ignite lighter away from face and clothing.  | Present   | -      |
|                           | ASTM F400-04, Section 7.5   | All         | Use one of the following as appropriate for the lighter type:  | See Below | -      |
|                           | ASTM F400-04, Section 7.5.1 | All         | Be sure flame is out after use. (Self-extinguishing lighters)  | Present   | -      |
|                           | ASTM F400-04, Section 7.5.2 | All         | This lighter does not self-extinguish; close cover to put out. (Non-self-extinguishing lighters)   | N/A       | -      |
|                           | ASTM F400-04, Section 7.6   | All         | For all lighters, the safety information may include the substance of the following as appropriate for the lighter type:   | See Below | -      |
|                           | ASTM F400-04, Section 7.6.1 | All         | Contains flammable gas under pressure.   | Present   | -      |
|                           | ASTM F400-04, Section 7.6.2 | All         | Contains flammable fluid.  | N/A       | -      |
|                           | ASTM F400-04, Section 7.6.3 | All         | When filled, will contain flammable fluid.   | N/A       | -      |
|                           | ASTM F400-04, Section 7.6.4 | All         | Never expose to heat above 120°F (49°C) or to prolonged sunlight.  | Present   | -      |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF

**MC-4085-US  
Lighters (ASTM F400)**

| Evaluation                      | Citation/Method                 | No. Samples | Criteria  | Results                 | Rating |
|---------------------------------|---------------------------------|-------------|---|-------------------------|--------|
|                                 | ASTM F400-04, Section 7.6.5     | All         | Never puncture or put in fire.  | Present                 | -      |
|                                 | ASTM F400-04, Section 7.6.6     | All         | Extreme heat is present above the visible flame. Extra care should be taken to prevent burn injury or fire. (premixing burner lighters)                                   | N/A                     | -      |
|                                 | ASTM F400-04, Section 7.6.7     | All         | Do not keep lit for more than 10 seconds. (premixing burner lighters)   | N/A                     | -      |
|                                 | ASTM F400-04, Section 7.7       | All         | Refillable gas lighters shall be accompanied by specific instructions as to the correct procedure to accomplish the refill operation, including type of fuel recommended. | Not Present             | -      |
|                                 | ASTM F400-04, Section 7.8.1     | All         | Fluid lighters shall be accompanied by the substance of the following:  | See Below               | -      |
|                                 | ASTM F400-04, Section 7.8.1.1   | All         | Fill only with the type of fluid recommended by the manufacturer.   | Not Present             | -      |
|                                 | ASTM F400-04, Section 7.8.1.2   | All         | Fill slowly, never overfill.  | Not Present             | -      |
|                                 | ASTM F400-04, Section 7.8.1.3   | All         | Wipe lighter and hands dry before igniting.   | Not Present             | -      |
| Product Markings                | ASTM F400-04, Section 8         | All         | All lighters shall bear a permanent logo or name that identifies the manufacturer or distributor.   | Not Present             | -      |
| <b>PACKAGING</b>                |                                 |             |   |                         |        |
| Retail Shelf Packaging          | TM-HL-0002                      | All         | Shall have final retail shelf packaging with scannable UPC stamp/label. Scanned numbers shall match as per supplied UPC label.  | NT – Per Client Request | -      |
| <b>ANALYTICAL</b>               |                                 |             |   |                         |        |
| * Lead In Surface Coating       | ASTM E1613-04 / E1645-01 (Mod.) | 1           | Shall not exceed 600 ppm (0.06% by weight) total lead.  | NT – Not Requested      | -      |
| <b>PHYSICAL CHARACTERISTICS</b> |                                 |             |   |                         |        |
| Dimensions (If Specified)       | TM-HL-0001                      | 1           | Report overall dimensions. L x W x H (cm)   | 8.3 x 2 x 1.3 cm        | -      |
| Weight (If Specified)           | TM-HL-0001                      | 1           | Report weight.  | 19.1 g                  | -      |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF

**MC-4085-US  
Lighters (ASTM F400)**

| Evaluation                            | Citation/Method   | No. Samples | Criteria   | Results             | Rating |
|---------------------------------------|---|-------------|--|---------------------|--------|
| <b>CONSTRUCTION &amp; WORKMANSHIP</b> |   |             |  |                     |        |
| Defects                               | TM-HL-0002  | All         | Shall be free of aesthetic defects and shall meet the structural requirements as tested under IV. Performance.   | M                   | PASS   |
| <b>PERFORMANCE</b>                    |   |             |  |                     |        |
| Flame Generation                      | ASTM F400-04, Standard Consumer Safety Specification for Lighters | 1           | Lighters shall require a deliberate manual operation to produce a flame. These operations shall conform to at least one of the following requirements: | See Below           | -      |
|                                       | ASTM F400-04, Section 4.1.1                                       | 1           | A system such that positive action on the part of the consumer is required to generate and maintain a flame.   | M                   | PASS   |
|                                       | ASTM F400-04, Section 4.1.2                                       | 1           | A system that requires two or more independent motions to generate a flame.  | NT – Meets Previous | -      |
|                                       | ASTM F400-04, Section 4.1.3                                       | 1           | A system that requires an actuating force equal to or greater than 3.4 lbf (15 N) to generate a flame.   | NT – Meets Previous | -      |
| Flame Control                         | ASTM F400-04, Section 4.2   | 1           | The maximum attainable flame height for lighters shall be limited with a setting or by product design, or both.  | M                   | PASS   |
|                                       | ASTM F400-04, Section 4.2.1 when tested in accordance with 8.1.   | 1           | Nonadjustable fluid lighters:  | See Below           | -      |
|                                       |   | 1           | Shall not be capable of producing a flame height greater than 4.75 in. (120 mm).   | N/A – Adjustable    | -      |
|                                       | ASTM F400-04, Section 4.2.2 when tested in accordance with 8.1.   | 1           | Nonadjustable postmixing and premixing burner lighters:  | See Below           | -      |
|                                       |   | 1           | Shall have a maximum attainable flame height of no more than 2 in. (50 mm).  | N/A – Adjustable    | -      |
|                                       | ASTM F400-04, Section 4.2.3 when tested in accordance with 8.1.   | 1           | Adjustable postmixing burner Lighters:   | See Below           | -      |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF

**MC-4085-US  
Lighters (ASTM F400)**

| Evaluation              | Citation/Method  | No. Samples | Criteria  | Results       | Rating |
|-------------------------|--|-------------|---|---------------|--------|
|                         |  | 1           | Shall not be capable of producing a flame height greater than 4.75 in. (120 mm) when deliberately adjusted by the consumer for maximum flame height.  | M             | PASS   |
|                         | ASTM F400-04, Section 4.2.4, when tested in accordance with 8.1. | 1           | Adjustable premixing burner lighters:   | See Below     |        |
|                         |  | 1           | Shall not be capable of producing a flame height in excess of 3 in. (75 mm) when deliberately adjusted by the consumer for maximum flame height..   | N/A – Postmix | -      |
|                         | ASTM F400-04, Section 4.2.5, when tested in accordance with 8.1. |             | Adjustable postmixing burner lighters:  | See Below     | -      |
|                         |  | 1           | The first strike will not produce a flame height in excess of 4 in. (100 mm).   | M             | PASS   |
|                         | ASTM F400-04, Section 4.2.6, when tested in accordance with 8.1. | 1           | Adjustable premixing burner lighters:   | See Below     | -      |
|                         |  | 1           | The first strike will not produce a flame height in excess of 2.5 in. (60 mm).  | N/A – Postmix | -      |
|                         | ASTM F400-04, Section 4.2.7, when tested in accordance with 8.1. | 1           | All adjustable flame height lighters:   | See Below     | -      |
|                         |  | 1           | Shall not be capable of producing a flame height in excess of 2 in. (50 mm) when set at the lowest possible flame height..  | M             | PASS   |
| Flame Height Adjustment | ASTM F400-04, Section 4.3  | 1           | Adjustable lighters shall require a deliberate manual operation to increase the flame height when the lighter is used in the normal fashion.  | M             | PASS   |
|                         | ASTM F400-04, Section 4.3.1                                      | 1           | Flame control actuators protrude from the body of the lighter. Shall require a minimum actuating force of 0.25 lbf (1 N) applied over the entire range of adjustment in a tangential direction. | M – 2.44 lb   | PASS   |
|                         | ASTM F400-04, Section 4.3.2                                      | 1           | Adjustable gas lighters having rotary movement flame control actuators approximately at right angles to the flame shall perform as follows:   | See Below     | -      |



BUREAU  
VERITAS

BV Lab Number: (5106) 010-0101R  
Technician Name: JRF

MC-4085-US  
Lighters (ASTM F400)

| Evaluation                         | Citation/Method   | No. Samples | Criteria   | Results   | Rating |
|------------------------------------|---|-------------|--|-----------|--------|
|                                    | ASTM F400-04, Section 4.3.2.1                                   | 1           | The flame control actuator is at the top of the lighter.   | M         | PASS   |
|                                    |   | 1           | Moving the actuator to the left shall produce a decrease in flame height.  | M         | PASS   |
|                                    | ASTM F400-04, Section 4.3.2.2                                   | 1           | The flame control actuator is at the bottom of the lighter.  | N/A       | -      |
|                                    |   | 1           | A clockwise movement shall produce a decrease in flame height.   | N/A       | -      |
|                                    | ASTM F400-04, Section 4.3.3                                     | 1           | Adjustable gas lighters requiring motion of the flame control actuator approximately parallel to the flame axis shall decrease or increase the flame height according to the direction of the movement.  | N/A       | -      |
|                                    | ASTM F400-04, Section 4.3.4                                     | 1           | Adjustable flame height lighters.  | See Below | -      |
|                                    |   | 1           | Shall indicate the direction of movement to produce a higher or lower flame height.  | M         | PASS   |
|                                    | ASTM F400-04, Section 4.3.4                                     | 1           | On lighters whose adjusting mechanisms conform to sections 4.3.2 and 4.3.3, the direction of movement shall be permanently imprinted or engraved on the lighter or may be of a nonpermanent tag or stick-on label, in the vicinity of the adjusting mechanism and be readily visible and understandable. | Meets     | PASS   |
|                                    | ASTM F400-04, Section 4.3.5                                     | 1           | On lighters whose adjusting mechanisms do not conform to sections 4.3.2 and 4.3.3, the direction of movement shall be permanently imprinted or engraved on the lighter, in the vicinity of the adjusting mechanism and be readily visible and understandable.  | N/A       | -      |
| Spitting or Sputtering and Flaring | ASTM F400-04, Section 4.4, when tested in accordance with 8.2.  | 1           | Gas lighters when set at the maximum flame height, shall exhibit no spitting or sputtering, or flaring.  | M         | PASS   |
| Flame Extinction                   | ASTM F400-04, Section 4.5.1, when tested in accordance with 8.3 | 1           | Adjustable postmixing burner lighters, after a 5-second burn at maximum flame height, when extinguished in the intended manner, shall have any exposed flame completely extinguished within 2 seconds.   | M         | PASS   |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF

**MC-4085-US  
Lighters (ASTM F400)**

| Evaluation              | Citation/Method  | No. Samples | Criteria   | Results          |       | Rating |
|-------------------------|--|-------------|--|------------------|-------|--------|
|                         | ASTM F400-04, Section 4.5.2, when tested in accordance with 8.3.         | 1           | Adjustable postmixing burner lighters at a flame height of 2 in. (50 mm), or the maximum height of adjustment allows, or nonadjustable postmixing burner lighters at their permanently set flame heights, after a 10 second burn:  | See Below        |       | -      |
|                         |  | 1           | When extinguished in the intended manner, shall have any exposed flame completely extinguished within 2 seconds after such action is completed.  | M                |       | PASS   |
|                         |  | 1           | For gas lighters that have shields, an additional 2 second afterburn is acceptable if the flame height does not extend above the shield.   | Meets Previous   |       | -      |
|                         | ASTM F400-04, Section 4.5.3, when tested in accordance with 8.3.         | 1           | Adjustable premixing burner lighters, after a 5 second burn at maximum flame height:   | See Below        |       | -      |
|                         |  | 1           | When extinguished in the intended manner, shall have any exposed flame completely extinguished in no more than 5 seconds.  | N/A - Postmixing |       | -      |
|                         | ASTM F400-04, Section 4.5.4, when tested in accordance with 8.3.         | 1           | Adjustable premixing burner lighters, when set at a flame height of 2 in. (50 mm) or the maximum flame height the adjustment allows, if lower than 50 mm, or nonadjustable premixing burner lighters at their permanently set flame heights, after a 10 second burn, when closed in the intended manner: | See Below        |       | -      |
|                         |  | 1           | Shall have any exposed flame completely extinguished in no more than 5 seconds.  | N/A - Postmixing |       | -      |
| Volumetric Displacement | ASTM F400-04, Section 4.6, when tested in accordance with 8.14.          | 1           | Liquid portion of the fuel shall not exceed 85% of the volumetric capacity of the fuel chamber.  | NM – 88.9 %      |       | FAIL   |
| Drop Test               | ASTM F400-04, Section 5.2.1, when tested in accordance with Section 8.4. | 1           | Postmixing and premixing burner lighters must be capable of withstanding three separate 5-ft. (1.5 m) drops.   | See Below        |       | -      |
|                         |  |             |  | 23°C             | -10°C |        |
|                         |  | 1           | Without fuel tank fragmentation.   | M                | M     | PASS   |
|                         |  | 1           | Without resulting in sustained self-ignition.  | M                | M     | PASS   |



**BUREAU  
VERITAS**

BV Lab Number: (5106) 010-0101R  
 Technician Name: JRF

**MC-4085-US  
Lighters (ASTM F400)**

| Evaluation       | Citation/Method  | No. Samples | Criteria   | Results   |   | Rating |
|------------------|--|-------------|--|-----------|---|--------|
|                  |  | 1           | Without gas escape exceeding 15 mg/min.  | M         | M | PASS   |
|                  |  | 1           | Without impairing the subsequent safe operation of the lighter.  | M         | M | PASS   |
|                  | ASTM F400-04, Section 5.2.2, when tested in accordance with Section 8.3. | 1           | Fluid lighters must be capable of withstanding three separate 5 ft. (1.5 m) drops.   | See Below |   | -      |
|                  |  | 1           | Without fuel tank rupture.   | N/A - Gas |   | -      |
|                  | ASTM F400-04, Section 5.2.3  | 1           | Without resulting in sustained self-ignition.  | N/A - Gas |   | -      |
|                  |  | 1           | Without impairing the subsequent safe operation of the lighter.  | N/A - Gas |   | -      |
|                  | ASTM F400-04, Section 5.2.3  | 1           | Lighters that are still operable in the intended manner after testing, sections 5.2.1 or 5.2.2, shall be capable of meeting all the applicable requirements of section 4.                                    | N/A - Gas |   | -      |
| Temperature Test | ASTM F400-04, Section 5.3, when tested in accordance with Section 8.5.   | 1           | Lighters shall be capable of withstanding a temperature of 149°F (65°C) for 4 hours.   | M         |   | PASS   |
|                  |  | 1           | Lighters that are still operable in the intended manner shall be capable after return to 73 ± 4°F (23 ± 2°C) of meeting the applicable requirements in section 4.  | M         |   | PASS   |
| Burning Test     | ASTM F400-04, Section 5.4  | 1           | Adjustable gas lighters set at maximum, nonadjustable gas lighters at their permanently set flame height, or fluid type lighters:  | See Below |   | -      |
|                  |  | 1           | Shall be capable of withstanding a burning time of 5 seconds in any hand-held attitude without evidence of any burning or distortion of components so as to cause a hazardous condition.                     | M         |   | PASS   |
|                  | ASTM F400-04, Section 5.4.1  | 1           | Adjustable gas lighters set at 50 mm (2 inches) or the maximum flame height the adjustment allows if lower than 50 mm, nonadjustable gas lighters set at the permanent flame height, or fluid type lighters: | See Below |   | -      |



BUREAU  
VERITAS

BV Lab Number: (5106) 010-0101R  
Technician Name: JRF

MC-4085-US  
Lighters (ASTM F400)

| Evaluation            | Citation/Method   | No. Samples | Criteria   | Results   | Rating |
|-----------------------|---|-------------|--|-----------|--------|
|                       |   | 1           | Shall be capable of withstanding a burning time of 10 seconds in any hand-held attitude with the lighter in a position 45° below the horizontal with no burning or distortion of components so as to cause hazardous conditions. | M         | PASS   |
| Continuous Burn       | ASTM F400-04, Section 5.5, when tested in accordance with Section 8.6.        | 1           | Adjustable gas lighters, with flame set at 2 inches (50 mm) or the maximum flame height the adjustment allows if lower than 50 mm, nonadjustable gas lighters set at permanent flame height, or fluid type lighters:             | See Below | -      |
|                       |   | 1           | Shall be capable of withstanding a continuous burning time of 2 minutes with the flame in a vertical attitude without causing a hazardous condition.   | M         | PASS   |
| Cycling Burn          | ASTM F400-04, Section 5.6, when tested in accordance with Section 8.7.        | 1           | Adjustable gas lighters, with flame set at 2 inches (50 mm) or the maximum flame height the adjustment allows if lower than 50 mm, nonadjustable gas lighters set at permanent flame height, or fluid type lighters:             | See Below | -      |
|                       |   | 1           | Shall be capable of withstanding a burning time of 20 seconds, repeated 10 times.  | NM        | FAIL   |
| External Finish       | ASTM F400-04, Section 5.7   | 1           | Lighters shall have no external sharp edges that could cause accidental cuts or abrasions to the consumer when handled or used in the intended manner.   | M         | PASS   |
| Compatibility         | ASTM F400-04, Section 5.8 when tested in accordance with 8.8 and 8.9          | 1           | Components of gas and fluid lighters that come in contact with the fuel recommended shall not deteriorate after exposure so as to fail any of the criteria herein or allow gas to escape exceeding 15 mg/minute.                 | M         | PASS   |
| Pressure Tests        | ASTM F400-04, Section 5.9, when tested in accordance with Section 8.10.       | 1           | Gas lighters shall be capable of withstanding an internal pressure of two times the vapor pressure occurring at 131°F (55°C) of the fuel recommended by the manufacturer.  | M         | PASS   |
| Refilling of Lighters | ASTM F400-04, Section 6.1, when tested in accordance with Section 8.11 – 8.13 | 1           | Refillable fluid lighters shall include specific instructions and warnings as applicable in accordance with section 7.   | N/A       | -      |



BUREAU  
VERITAS

BV Lab Number: (5106) 010-0101R  
Technician Name: JRF

MC-4085-US  
Lighters (ASTM F400)

| Evaluation    | Citation/Method   | No. Samples | Criteria  | Results             | Rating |
|---------------|---|-------------|---|---------------------|--------|
|               | ASTM F400-04, Section 6.2, when tested in accordance with Section 8.11. | 1           | Refillable fluid lighters having a sealed fluid reservoir shall be free of fuel leakage from both the sealed reservoir and sealing closure.   | N/A                 | -      |
|               | ASTM F400-04, Section 6.3   | 1           | Refillable gas lighters shall have specific training instructions and warnings as applicable in accordance with section 7.  | NM                  | DATA   |
|               | ASTM F400-04, Section 6.4, when tested in accordance with Section 8.13. | 1           | Refillable gas lighters:<br>The refilling valve in a pressurized fuel tank lighter shall be secure enough so as not to allow an escape of gas exceeding 15 mg/min.                                      | M                   | DATA   |
| Certification | 16 CFR 1210.3   | 1           | Certification Showing Qualification Tests For Child Resistance Has Been Conducted Using Appropriate Surrogate Lighters And Child Panels Specified In The Regulations Must Be Submitted For Verification | NT – Client Request | -      |

Key:

M Meets  
 NA Not Applicable  
 \* Additional Charge For This Test

NM Does Not Meet  
 NT Not Tested  
 \*\* Mandatory Requirement

|  |    |
|--|----|
| No. Of Samples Required For Complete Testing:      | 20 |
| No. Of (Fully Packed) Cartons For Transit Testing: | 1  |
| No. Of Working Days For Complete Testing:          | 7  |

Client Approval:

Creation Date: June 3, 2003  
 Editorial Revision Date: October 18, 2005  
 Pricing Review Date: January 28, 2005  
 Technical Review Date:

EXHIBIT #1




PHOTO SHOWS SELF SUSTAINED IGNITION